










Ron

Adjustable trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 60 mm
-  0°~15°
-  0°~355°
-  Matte White (MW)
-  Matte Black (MB)
-  Matte Silver (MS)
-  Matte Gold (MG)



Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 6W	15°	02.6001.MW	02.6002.MW	02.6003.MW	02.6004.MW	02.6033.MW
		02.6001.MB	02.6002.MB	02.6003.MB	02.6004.MB	02.6033.MB
		02.6001.MS	02.6002.MS	02.6003.MS	02.6004.MS	02.6033.MS
		02.6001.MG	02.6002.MG	02.6003.MC	02.6004.MG	02.6033.MG
	24°	02.6005.MW	02.6006.MW	02.6007.MW	02.6008.MW	02.6034.MW
		02.6005.MB	02.6006.MB	02.6007.MB	02.6008.MB	02.6034.MB
		02.6005.MS	02.6006.MS	02.6007.MS	02.6008.MS	02.6034.MS
		02.6005.MG	02.6006.MG	02.6007.MG	02.6008.MG	02.6034.MG
	36°	02.6009.MW	02.6010.MW	02.6011.MW	02.6012.MW	02.6035.MW
		02.6009.MB	02.6010.MB	02.6011.MB	02.6012.MB	02.6035.MB
		02.6009.MS	02.6010.MS	02.6011.MS	02.6012.MS	02.6035.MS
		02.6009.MG	02.6010.MG	02.6011.MG	02.6012.MG	02.6035.MG
50°	02.6013.MW	02.6014.MW	02.6015.MW	02.6016.MW	02.6036.MW	
	02.6013.MB	02.6014.MB	02.6015.MB	02.6016.MB	02.6036.MB	
	02.6013.MS	02.6014.MS	02.6015.MS	02.6016.MS	02.6036.MS	
	02.6013.MG	02.6014.MG	02.6015.MG	02.6016.MG	02.6036.MG	

Dimming: On/Off, 1-10V, DALI, TRIAC
 UGR: ≤15
 SDCM: ≤3
 Luminous efficacy: 78lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 150mA

