






Ron

Adjustable trimless Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 60 mm
-  0°~15°
-  0°~355°
-  Matte White (MW)
-  Matte Black (MB)
-  Matte Silver (MS)
-  Matte Gold (MG)



Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 6W	15°	11.6001.MW	11.6002.MW	11.6003.MW	11.6004.MW	11.6033.MW
		11.6001.MB	11.6002.MB	11.6003.MB	11.6004.MB	11.6033.MB
		11.6001.MS	11.6002.MS	11.6003.MS	11.6004.MS	11.6033.MS
		11.6001.MG	11.6002.MG	11.6003.MC	11.6004.MG	11.6033.MG
	24°	11.6005.MW	11.6006.MW	11.6007.MW	11.6008.MW	11.6034.MW
		11.6005.MB	11.6006.MB	11.6007.MB	11.6008.MB	11.6034.MB
		11.6005.MS	11.6006.MS	11.6007.MS	11.6008.MS	11.6034.MS
		11.6005.MG	11.6006.MG	11.6007.MG	11.6008.MG	11.6034.MG
	36°	11.6009.MW	11.6010.MW	11.6011.MW	11.6012.MW	11.6035.MW
		11.6009.MB	11.6010.MB	11.6011.MB	11.6012.MB	11.6035.MB
		11.6009.MS	11.6010.MS	11.6011.MS	11.6012.MS	11.6035.MS
		11.6009.MG	11.6010.MG	11.6011.MG	11.6012.MG	11.6035.MG
	50°	11.6013.MW	11.6014.MW	11.6015.MW	11.6016.MW	11.6036.MW
		11.6013.MB	11.6014.MB	11.6015.MB	11.6016.MB	11.6036.MB
		11.6013.MS	11.6014.MS	11.6015.MS	11.6016.MS	11.6036.MS
		11.6013.MG	11.6014.MG	11.6015.MG	11.6016.MG	11.6036.MG

Dimming: On/Off, 1-10V, DALI, TRIAC
 UGR: ≤15
 SDCM: ≤3
 Luminous efficacy: 78lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 150mA

