





OT (4 CIRCUIT TRACK)

Track Mounted Luminaire

-  Ceiling Track
-  AC 220V~240V
-  Ra 95
-  Reflector
-  Class II
-  0°~90°
-  0°~355°
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 25W	15°	20.6513.WH	20.6514.WH	20.6515.WH	20.6516.WH
		20.6513.BK	20.6514.BK	20.6515.BK	20.6516.BK
		20.6513.CH	20.6514.CH	20.6515.CH	20.6516.CH
	24°	20.6517.WH	20.6518.WH	20.6519.WH	20.6520.WH
		20.6517.BK	20.6518.BK	20.6519.BK	20.6520.BK
		20.6517.CH	20.6518.CH	20.6519.CH	20.6520.CH
	36°	20.6521.WH	20.6522.WH	20.6523.WH	20.6524.WH
		20.6521.BK	20.6522.BK	20.6523.BK	20.6524.BK
		20.6521.CH	20.6522.CH	20.6523.CH	20.6524.CH

Dimming:
 UGR:
 SDCM:
 Luminous efficacy:
 luminaire Lifetime:
 Material:
 Working Temperature (°C):
 Transformer availability:

On/Off
 ≤13
 ≤3
 80lm/W
 50000h (L80B50, T a25° C)
 Aluminium
 -20° C ~ +45° C
 AC 220V~240V integrated guide rail head

