





OT (4 CIRCUIT TRACK)

Track Mounted Luminaire

-  Ceiling Track
-  AC 220V~240V
-  Ra 95
-  Reflector
-  Class II
-  0°~90°
-  0°~355°
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 18W	15°	20.5525.WH 20.5525.BK 20.5525.CH	20.5526.WH 20.5526.BK 20.5526.CH	20.5527.WH 20.5527.BK 20.5527.CH	20.5528.WH 20.5528.BK 20.5528.CH
	24°	20.5529.WH 20.5529.BK 20.5529.CH	20.5530.WH 20.5530.BK 20.5530.CH	20.5531.WH 20.5531.BK 20.5531.CH	20.5532.WH 20.5532.BK 20.5532.CH
	36°	20.5533.WH 20.5533.BK 20.5533.CH	20.5534.WH 20.5534.BK 20.5534.CH	20.5535.WH 20.5535.BK 20.5535.CH	20.5536.WH 20.5536.BK 20.5536.CH

Dimming:
 UGR:
 SDCM:
 Luminous efficacy:
 luminaire Lifetime:
 Material:
 Working Temperature (°C):
 Transformer availability:

On/Off
 ≤13
 ≤3
 80lm/W
 50000h (L80B50, T a25° C)
 Aluminium
 -20° C ~ +45° C
 Driver built-in

