





OT (4 CIRCUIT TRACK)

Track Mounted Luminaire

-  Ceiling Track
-  AC 220V~240V
-  Ra 95
-  Reflector
-  Class II
-  0°~90°
-  0°~355°
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 18W	15°	20.5513.WH 20.5513.BK 20.5513.CH	20.5514.WH 20.5514.BK 20.5514.CH	20.5515.WH 20.5515.BK 20.5515.CH	20.5516.WH 20.5516.BK 20.5516.CH
	24°	20.5517.WH 20.5517.BK 20.5517.CH	20.5518.WH 20.5518.BK 20.5518.CH	20.5519.WH 20.5519.BK 20.5519.CH	20.5520.WH 20.5520.BK 20.5520.CH
	36°	20.5521.WH 20.5521.BK 20.5521.CH	20.5522.WH 20.5522.BK 20.5522.CH	20.5523.WH 20.5523.BK 20.5523.CH	20.5524.WH 20.5524.BK 20.5524.CH

Dimming: On/Off
 UGR: ≤13
 SDCM: ≤3
 Luminous efficacy: 80lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: AC 220V~240V integrated guide rail head

