




OT (4 CIRCUIT TRACK)

Track Mounted Luminaire

-  Ceiling Track
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  0°~90°
-  0°~355°
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 15W	15°	20.4513.WH 20.4513.BK 20.4513.CH	20.4514.WH 20.4514.BK 20.4514.CH	20.4515.WH 20.4515.BK 20.4515.CH	20.4516.WH 20.4516.BK 20.4516.CH
	24°	20.4517.WH 20.4517.BK 20.4517.CH	20.4518.WH 20.4518.BK 20.4518.CH	20.4519.WH 20.4519.BK 20.4519.CH	20.4520.WH 20.4520.BK 20.4520.CH
	36°	20.4521.WH 20.4521.BK 20.4521.CH	20.4522.WH 20.4522.BK 20.4522.CH	20.4523.WH 20.4523.BK 20.4523.CH	20.4524.WH 20.4524.BK 20.4524.CH

Dimming:
 UGR:
 SDCM:
 Luminous efficacy:
 luminaire Lifetime:
 Material:
 Working Temperature (°C):
 Transformer availability:

On/Off
 ≤13
 ≤3
 80lm/W
 50000h (L80B50, T a25° C)
 Aluminium
 -20° C ~ +45° C
 AC 220V~240V integrated guide rail head

