


# OT

Adjustable trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 45 mm
-  0°~90°
-  0°~355°
-  White(WH)
-  Black(BK)
-  Chrome(CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 10W	15°	03.4501.WH 03.4501.BK 03.4501.CH	03.4502.WH 03.4502.BK 03.4502.CH	03.4503.WH 03.4503.BK 03.4503.CH	03.4504.WH 03.4504.BK 03.4504.CH	03.4525.WH 03.4525.BK 03.4525.CH
	24°	03.4505.WH 03.4505.BK 03.4505.CH	03.4506.WH 03.4506.BK 03.4506.CH	03.4507.WH 03.4507.BK 03.4507.CH	03.4508.WH 03.4508.BK 03.4508.CH	03.4526.WH 03.4526.BK 03.4526.CH
	36°	03.4509.WH 03.4509.BK 03.4509.CH	03.4510.WH 03.4510.BK 03.4510.CH	03.4511.WH 03.4511.BK 03.4511.CH	03.4512.WH 03.4512.BK 03.4512.CH	03.4527.WH 03.4527.BK 03.4527.CH

Dimming: On/Off, TRIAC, 1-10V, DALI  
 UGR: ≤ 13  
 SDCM: ≤ 3  
 Luminous efficacy: 80lm/W  
 luminaire Lifetime: 50000h ( L80B50, T a25° C )  
 Material: Aluminium  
 Working Temperature ( °C ): -20° C ~ +45° C  
 Transformer availability: LED DC 36V 250mA

