


OT

Adjustable trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Reflector
-  Class II
-  Ø 45 mm
-  0°~90°
-  0°~355°
-  White(WH)
-  Black(BK)
-  Chrome(CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 25W	15°	03.6501.WH 03.6501.BK 03.6501.CH	03.6502.WH 03.6502.BK 03.6502.CH	03.6503.WH 03.6503.BK 03.6503.CH	03.6504.WH 03.6504.BK 03.6504.CH
	24°	03.6505.WH 03.6505.BK 03.6505.CH	03.6506.WH 03.6506.BK 03.6506.CH	03.6507.WH 03.6507.BK 03.6507.CH	03.6508.WH 03.6508.BK 03.6508.CH
	36°	03.6509.WH 03.6509.BK 03.6509.CH	03.6510.WH 03.6510.BK 03.6510.CH	03.6511.WH 03.6511.BK 03.6511.CH	03.6512.WH 03.6512.BK 03.6512.CH

Dimming: On/Off, TRIAC, 1-10V, DALI
 UGR: ≤13
 SDCM: ≤3
 Luminous efficacy: 80lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 500mA

