

recessed downlight

# Cabin pro



Fixed Downlight  
trim or trimless  
10W or 15W

ESPRESSO €2.00  
CAFFÈ €2.00  
CAPPUCINO €3.50












CAFFÈ MACCHIATO €2.50  
CAFFÈ LATTE €2.50  
CAFFÈ MACCHIATO €2.50  
CAFFÈ LATTE €2.50  
CAFFÈ MACCHIATO €2.50  
CAFFÈ LATTE €2.50





# Cabin pro

Fixed trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Reflector
-  Class II
-  Ø 70 mm
-  Matte White (MW)
-  Matte Black (MB)
-  Matte Silver (MS)
-  Matte Copper (MC)
-  Matte Gold (MG)














Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 10W	▲ 24°	01.7051.MW	01.7052.MW	01.7053.MW	01.7054.MW	01.7075.MW
		01.7051.MB	01.7052.MB	01.7053.MB	01.7054.MB	01.7075.MB
		01.7051.MS	01.7052.MS	01.7053.MS	01.7054.MS	01.7075.MS
		01.7051.MC	01.7052.MC	01.7053.MC	01.7054.MC	01.7075.MC
		01.7051.MG	01.7052.MG	01.7053.MG	01.7054.MG	01.7075.MG
	▲ 38°	01.7055.MW	01.7056.MW	01.7057.MW	01.7058.MW	01.7076.MW
		01.7055.MB	01.7056.MB	01.7057.MB	01.7058.MB	01.7076.MB
		01.7055.MS	01.7056.MS	01.7057.MS	01.7058.MS	01.7076.MS
		01.7055.MC	01.7056.MC	01.7057.MC	01.7058.MC	01.7076.MC
		01.7055.MG	01.7056.MG	01.7057.MG	01.7058.MG	01.7076.MG
	▲ 55°	01.7059.MW	01.7060.MW	01.7061.MW	01.7062.MW	01.7077.MW
		01.7059.MB	01.7060.MB	01.7061.MB	01.7062.MB	01.7077.MB
		01.7059.MS	01.7060.MS	01.7061.MS	01.7062.MS	01.7077.MS
		01.7059.MC	01.7060.MC	01.7061.MC	01.7062.MC	01.7077.MC
		01.7059.MG	01.7060.MG	01.7061.MG	01.7062.MG	01.7077.MG


Dimming: On/Off, 1-10V, DALI, TRIAC  
 UGR: ≤8  
 SDCM: ≤3  
 Luminous efficacy: 78lm/W  
 luminaire Lifetime: 50000h ( L80B50, T a25° C )  
 Material: Aluminium  
 Working Temperature ( °C): -20° C ~ +45° C  
 Transformer availability: LED DC 36V 250mA



# Cabin pro

Fixed trimless Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Reflector
-  Class II
-  Ø 120 mm
-  Matte White (MW)
-  Matte Black (MB)
-  Matte Silver (MS)
-  Matte Copper (MC)
-  Matte Gold (MG)














Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 10W	▲ 24°	10.7051.MW	10.7052.MW	10.7053.MW	10.7054.MW	10.7075.MW
		10.7051.MB	10.7052.MB	10.7053.MB	10.7054.MB	10.7075.MB
		10.7051.MS	10.7052.MS	10.7053.MS	10.7054.MS	10.7075.MS
		10.7051.MC	10.7052.MC	10.7053.MC	10.7054.MC	10.7075.MC
		10.7051.MG	10.7052.MG	10.7053.MG	10.7054.MG	10.7075.MG
	▲ 38°	10.7055.MW	10.7056.MW	10.7057.MW	10.7058.MW	10.7076.MW
		10.7055.MB	10.7056.MB	10.7057.MB	10.7058.MB	10.7076.MB
		10.7055.MS	10.7056.MS	10.7057.MS	10.7058.MS	10.7076.MS
		10.7055.MC	10.7056.MC	10.7057.MC	10.7058.MC	10.7076.MC
		10.7055.MG	10.7056.MG	10.7057.MG	10.7058.MG	10.7076.MG
	▲ 55°	10.7059.MW	10.7060.MW	10.7061.MW	10.7062.MW	10.7077.MW
		10.7059.MB	10.7060.MB	10.7061.MB	10.7062.MB	10.7077.MB
		10.7059.MS	10.7060.MS	10.7061.MS	10.7062.MS	10.7077.MS
		10.7059.MC	10.7060.MC	10.7061.MC	10.7062.MC	10.7077.MC
		10.7059.MG	10.7060.MG	10.7061.MG	10.7062.MG	10.7077.MG

Dimming: On/Off, 1-10V, DALI, TRIAC  
 UGR: ≤8  
 SDCM: ≤3  
 Luminous efficacy: 78lm/W  
 luminaire Lifetime: 50000h ( L80B50, T a25° C )  
 Material: Aluminium  
 Working Temperature ( °C): -20° C ~ +45° C  
 Transformer availability: LED DC 36V 250mA



# Cabin pro

Fixed trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Reflector
-  Class II
-  Ø 70 mm
-  Matte White (MW)
-  Matte Black (MB)
-  Matte Silver (MS)
-  Matte Copper (MC)
-  Matte Gold (MG)














Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 15W	▲ 24°	01.7063.MW	01.7064.MW	01.7065.MW	01.7066.MW	01.7078.MW
		01.7063.MB	01.7064.MB	01.7065.MB	01.7066.MB	01.7078.MB
		01.7063.MS	01.7064.MS	01.7065.MS	01.7066.MS	01.7078.MS
		01.7063.MC	01.7064.MC	01.7065.MC	01.7066.MC	01.7078.MC
		01.7063.MG	01.7064.MG	01.7065.MG	01.7066.MG	01.7078.MG
	▲ 38°	01.7067.MW	01.7068.MW	01.7069.MW	01.7070.MW	01.7079.MW
		01.7067.MB	01.7068.MB	01.7069.MB	01.7070.MB	01.7079.MB
		01.7067.MS	01.7068.MS	01.7069.MS	01.7070.MS	01.7079.MS
		01.7067.MC	01.7068.MC	01.7069.MC	01.7070.MC	01.7079.MC
		01.7067.MG	01.7068.MG	01.7069.MG	01.7070.MG	01.7079.MG
	▲ 55°	01.7071.MW	01.7072.MW	01.7073.MW	01.7074.MW	01.7080.MW
		01.7071.MB	01.7072.MB	01.7073.MB	01.7074.MB	01.7080.MB
		01.7071.MS	01.7072.MS	01.7073.MS	01.7074.MS	01.7080.MS
		01.7071.MC	01.7072.MC	01.7073.MC	01.7074.MC	01.7080.MC
		01.7071.MG	01.7072.MG	01.7073.MG	01.7074.MG	01.7080.MG


Dimming: On/Off, 1-10V, DALI, TRIAC  
 UGR: ≤8  
 SDCM: ≤3  
 Luminous efficacy: 78lm/W  
 luminaire Lifetime: 50000h ( L80B50, T a25° C )  
 Material: Aluminium  
 Working Temperature ( °C): -20° C ~ +45° C  
 Transformer availability: LED DC 36V 350mA



# Cabin pro

Fixed trimless Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Reflector
-  Class II
-  Ø 120 mm
-  Matte White (MW)
-  Matte Black (MB)
-  Matte Silver (MS)
-  Matte Copper (MC)
-  Matte Gold (MG)



Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 15W	▲ 24°	10.7063.MW	10.7064.MW	10.7065.MW	10.7066.MW	10.7078.MW
		10.7063.MB	10.7064.MB	10.7065.MB	10.7066.MB	10.7078.MB
		10.7063.MS	10.7064.MS	10.7065.MS	10.7066.MS	10.7078.MS
		10.7063.MC	10.7064.MC	10.7065.MC	10.7066.MC	10.7078.MC
		10.7063.MG	10.7064.MG	10.7065.MG	10.7066.MG	10.7078.MG
	▲ 38°	10.7067.MW	10.7068.MW	10.7069.MW	10.7070.MW	10.7079.MW
		10.7067.MB	10.7068.MB	10.7069.MB	10.7070.MB	10.7079.MB
		10.7067.MS	10.7068.MS	10.7069.MS	10.7070.MS	10.7079.MS
		10.7067.MC	10.7068.MC	10.7069.MC	10.7070.MC	10.7079.MC
		10.7067.MG	10.7068.MG	10.7069.MG	10.7070.MG	10.7079.MG
	▲ 55°	10.7071.MW	10.7072.MW	10.7073.MW	10.7074.MW	10.7080.MW
		10.7071.MB	10.7072.MB	10.7073.MB	10.7074.MB	10.7080.MB
		10.7071.MS	10.7072.MS	10.7073.MS	10.7074.MS	10.7080.MS
		10.7071.MC	10.7072.MC	10.7073.MC	10.7074.MC	10.7080.MC
		10.7071.MG	10.7072.MG	10.7073.MG	10.7074.MG	10.7080.MG

Dimming: On/Off, 1-10V, DALI, TRIAC  
 UGR: ≤8  
 SDCM: ≤3  
 Luminous efficacy: 78lm/W  
 luminaire Lifetime: 50000h ( L80B50, T a25° C )  
 Material: Aluminium  
 Working Temperature ( °C): -20° C ~ +45° C  
 Transformer availability: LED DC 36V 350mA





## OBT LIGHTING LIMITED

Unit G1 Capital House 61  
Amhurst Road, London,  
United Kingdom, E8 1LL  
services@obtlighting.cn  
Hotline : 400 090 2289

[www.obt.ltd](http://www.obt.ltd)



Floor 2, No. 979, Yunhan  
Road, Lingang New District,  
China (Shanghai) pilot Free  
Trade Zone  
services@obtlighting.cn  
Hotline : 400 090 2289

[www.obt.ltd](http://www.obt.ltd)

Office 5, 8/F, Mega Cube,  
8 Wang Kwong Road, Kowloon  
Bay, Kowloon, Hong Kong  
services@obtlighting.cn  
Hotline : 400 090 2289

[www.obt.ltd](http://www.obt.ltd)