










OT (2.0 SERIES)

-  Ceiling Track
-  DC 48V
-  Ra 95
-  Reflector
-  Class III
-  0°~90°
-  0°~355°
-  White(WH)
-  Black(BK)
-  Chrome(CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 18W	15°	32.5513.WH 32.5513.BK 32.5513.CH	32.5514.WH 32.5514.BK 32.5514.CH	32.5515.WH 32.5515.BK 32.5515.CH	32.5516.WH 32.5516.BK 32.5516.CH
	24°	32.5517.WH 32.5517.BK 32.5517.CH	32.4518.WH 32.4518.BK 32.4518.CH	32.5519.WH 32.5519.BK 32.5519.CH	32.5520.WH 32.5520.BK 32.5520.CH
	36°	32.5521.WH 32.5521.BK 32.5521.CH	32.5522.WH 32.5522.BK 32.5522.CH	32.5523.WH 32.5523.BK 32.5523.CH	32.5524.WH 32.5524.BK 32.5524.CH

Dimming: On/Off, 1-10V
 UGR: ≤16
 SDCM: ≤3
 Luminous efficacy: 74lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: DC 48V

