










OT (1.5 SERIES)

-  Ceiling Track
-  DC 48V
-  Ra 95
-  Reflector
-  Class III
-  0°~90°
-  0°~355°
-  White(WH)
-  Black(BK)
-  Chrome(CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 18W	15°	32.5501.WH 32.5501.BK 32.5501.CH	32.5502.WH 32.5502.BK 32.5502.CH	32.5503.WH 32.5503.BK 32.5503.CH	32.5504.WH 32.5504.BK 32.5504.CH
	24°	32.5505.WH 32.5505.BK 32.5505.CH	32.5506.WH 32.5506.BK 32.5506.CH	32.5507.WH 32.5507.BK 32.5507.CH	32.5508.WH 32.5508.BK 32.5508.CH
	36°	32.5509.WH 32.5509.BK 32.5509.CH	32.5510.WH 32.5510.BK 32.5510.CH	32.5511.WH 32.5511.BK 32.5511.CH	32.5512.WH 32.5512.BK 32.5512.CH

Dimming: On/Off, Knob
 UGR: ≤16
 SDCM: ≤3
 Luminous efficacy: 74lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: DC 48V

