










OT (1.5 SERIES)

-  Ceiling Track
-  DC 48V
-  Ra 95
-  Lens
-  Class III
-  0°~90°
-  0°~355°
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 8W	15°	32.3501.WH 32.3501.BK 32.3501.CH	32.3502.WH 32.3502.BK 32.3502.CH	32.3503.WH 32.3503.BK 32.3503.CH	32.3504.WH 32.3504.BK 32.3504.CH
	24°	32.3505.WH 32.3505.BK 32.3505.CH	32.3506.WH 32.3506.BK 32.3506.CH	32.3507.WH 32.3507.BK 32.3507.CH	32.3508.WH 32.3508.BK 32.3508.CH
	36°	32.3509.WH 32.3509.BK 32.3509.CH	32.3510.WH 32.3510.BK 32.3510.CH	32.3511.WH 32.3511.BK 32.3511.CH	32.3512.WH 32.3512.BK 32.3512.CH

Dimming: On/Off, Knob
 UGR: ≤16
 SDCM: ≤3
 Luminous efficacy: 74lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: DC 48V

