









OT (2.0 SERIES)

-  Ceiling Track
-  DC 48V
-  Ra 95
-  Lens
-  Class III
-  0°~90°
-  0°~355°
-  White(WH)
-  Black(BK)
-  Chrome(CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 8W	15°	32.3513.WH	32.3514.WH	32.3515.WH	32.3516.WH	32.3525.WH
		32.3513.BK	32.3514.BK	32.3515.BK	32.3516.BK	32.3525.BK
		32.3513.CH	32.3514.CH	32.3515.CH	32.3516.CH	32.3525.CH
	24°	32.3517.WH	32.3518.WH	32.3519.WH	32.3520.WH	32.3526.WH
		32.3517.BK	32.3518.BK	32.3519.BK	32.3520.BK	32.3526.BK
		32.3517.CH	32.3518.CH	32.3519.CH	32.3520.CH	32.3526.CH
	36°	32.3521.WH	32.3522.WH	32.3523.WH	32.3524.WH	32.3527.WH
		32.3521.BK	32.3522.BK	32.3523.BK	32.3524.BK	32.3527.BK
		32.3521.CH	32.3522.CH	32.3523.CH	32.3524.CH	32.3527.CH

Dimming: On/Off, 1-10V
 UGR: ≤16
 SDCM: ≤3
 Luminous efficacy: 74lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: DC 48V

