


OT (2.0 SERIES)

-  Ceiling Track
-  DC 48V
-  Ra 95
-  Lens
-  Class III
-  0°~90°
-  0°~355°
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 10W	15°	32.4513.WH	32.4514.WH	32.4515.WH	32.4516.WH	32.4549.WH
		32.4513.BK	32.4514.BK	32.4515.BK	32.4516.BK	32.4549.BK
		32.4513.CH	32.4514.CH	32.4515.CH	32.4516.CH	32.4549.CH
	24°	32.4517.WH	32.4518.WH	32.4519.WH	32.4520.WH	32.4550.WH
		32.4517.BK	32.4518.BK	32.4519.BK	32.4520.BK	32.4550.BK
		32.4517.CH	32.4518.CH	32.4519.CH	32.4520.CH	32.4550.CH
	36°	32.4521.WH	32.4522.WH	32.4523.WH	32.4524.WH	32.4551.WH
		32.4521.BK	32.4522.BK	32.4523.BK	32.4524.BK	32.4551.BK
		32.4521.CH	32.4522.CH	32.4523.CH	32.4524.CH	32.4551.CH

Dimming: On/Off, 1-10V
 UGR: ≤16
 SDCM: ≤3
 Luminous efficacy: 74lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: DC 48V

