












# OT (2.0 SERIES)

Magnetic Track Luminaire

-  Ceiling Track
-  DC 48V
-  Ra 95
-  Lens
-  Class III
-  0°~90°
-  0°~355°
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 15W	15°	32.4537.WH 32.4537.BK 32.4537.CH	32.4538.WH 32.4538.BK 32.4538.CH	32.4539.WH 32.4539.BK 32.4539.CH	32.4540.WH 32.4540.BK 32.4540.CH	32.4552.WH 32.4552.BK 32.4552.CH
	24°	32.4541.WH 32.4541.BK 32.4541.CH	32.4542.WH 32.4542.BK 32.4542.CH	32.4543.WH 32.4543.BK 32.4543.CH	32.4544.WH 32.4544.BK 32.4544.CH	32.4553.WH 32.4553.BK 32.4553.CH
	36°	32.4545.WH 32.4545.BK 32.4545.CH	32.4546.WH 32.4546.BK 32.4546.CH	32.4547.WH 32.4547.BK 32.4547.CH	32.4548.WH 32.4548.BK 32.4548.CH	32.4554.WH 32.4554.BK 32.4554.CH

Dimming: On/Off, 1-10V  
 UGR: ≤16  
 SDCM: ≤3  
 Luminous efficacy: 74lm/W  
 luminaire Lifetime: 50000h ( L80B50, T a25° C )  
 Material: Aluminium  
 Working Temperature ( °C): -20° C ~ +45° C  
 Transformer availability: DC 48V

