






OT (3 CIRCUIT TRACK)

Track Mounted Luminaire

-  Ceiling Track
-  AC 220V~240V
-  Ra 95
-  Reflector
-  Class II
-  0°~90°
-  0°~355°
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 25W	15°	20.6501.WH 20.6501.BK 20.6501.CH	20.6502.WH 20.6502.BK 20.6502.CH	20.6503.WH 20.6503.BK 20.6503.CH	20.6504.WH 20.6504.BK 20.6504.CH
	24°	20.6505.WH 20.6505.BK 20.6505.CH	20.6506.WH 20.6506.BK 20.6506.CH	20.6507.WH 20.6507.BK 20.6507.CH	20.6508.WH 20.6508.BK 20.6508.CH
	36°	20.6509.WH 20.6509.BK 20.6509.CH	20.6510.WH 20.6510.BK 20.6510.CH	20.6511.WH 20.6511.BK 20.6511.CH	20.6512.WH 20.6512.BK 20.6512.CH

Dimming: On/Off
 UGR: ≤13
 SDCM: ≤3
 Luminous efficacy: 80lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: AC 220V~240V integrated guide rail head

