


OT (3 CIRCUIT TRACK)

Track Mounted Luminaire

-  Ceiling Track
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  0°~90°
-  0°~355°
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 15W	15°	20.4501.WH 20.4501.BK 20.4501.CH	20.4502.WH 20.4502.BK 20.4502.CH	20.4503.WH 20.4503.BK 20.4503.CH	20.4504.WH 20.4504.BK 20.4504.CH
	24°	20.4505.WH 20.4505.BK 20.4505.CH	20.4506.WH 20.4506.BK 20.4506.CH	20.4507.WH 20.4507.BK 20.4507.CH	20.4508.WH 20.4508.BK 20.4508.CH
	36°	20.4509.WH 20.4509.BK 20.4509.CH	20.4510.WH 20.4510.BK 20.4510.CH	20.4511.WH 20.4511.BK 20.4511.CH	20.4512.WH 20.4512.BK 20.4512.CH

Dimming: On/Off
 UGR: ≤13
 SDCM: ≤3
 Luminous efficacy: 80lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: AC 220V~240V integrated guide rail head

