


OT (3 CIRCUIT TRACK)

Track Mounted Luminaire

-  Ceiling Track
-  AC 220V~240V
-  Ra 95
-  Reflector
-  Class II
-  0°~90°
-  0°~355°
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 18W	15°	20.5501.WH 20.5501.BK 20.5501.CH	20.5502.WH 20.5502.BK 20.5502.CH	20.5503.WH 20.5503.BK 20.5503.CH	20.5504.WH 20.5504.BK 20.5504.CH
	24°	20.5505.WH 20.5505.BK 20.5505.CH	20.5506.WH 20.5506.BK 20.5506.CH	20.5507.WH 20.5507.BK 20.5507.CH	20.5508.WH 20.5508.BK 20.5508.CH
	36°	20.5509.WH 20.5509.BK 20.5509.CH	20.5510.WH 20.5510.BK 20.5510.CH	20.5511.WH 20.5511.BK 20.5511.CH	20.5512.WH 20.5512.BK 20.5512.CH

Dimming:

UGR:

SDCM:

Luminous efficacy:

luminaire Lifetime:

Material:

Working Temperature (°C):

Transformer availability:

On/Off

≤13

≤3

80lm/W

50000h (L80B50, T a25° C)

Aluminium

-20° C ~ +45° C

AC 220V~240V integrated guide rail head

