

Mini Spot

Fixed trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 30 mm
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	4000K	2700~6500K
Max. 3W	15°	01.3001.WH	01.3002.WH	01.3003.WH	01.3019.WH
		01.3001.BK	01.3002.BK	01.3003.BK	01.3019.BK
		01.3001.CH	01.3002.CH	01.3003.CH	01.3019.CH
	24°	01.3004.WH	01.3005.WH	01.3006.WH	01.3020.WH
		01.3004.BK	01.3005.BK	01.3006.BK	01.3020.BK
		01.3004.CH	01.3005.CH	01.3006.CH	01.3020.CH
	36°	01.3007.WH	01.3008.WH	01.3009.WH	01.3021.WH
		01.3007.BK	01.3008.BK	01.3009.BK	01.3021.BK
		01.3007.CH	01.3008.CH	01.3009.CH	01.3021.CH

Dimming: On/Off, 1-10V, DALI, TRIAC
 UGR: ≤15
 SDCM: ≤3
 Luminous efficacy: 78lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 80mA

