








Mini Spot

Fixed trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 30 mm
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	4000K	2700~6500K
Max. 5W	15°	01.3010.WH	01.3011.WH	01.3012.WH	01.3022.WH
		01.3010.BK	01.3011.BK	01.3012.BK	01.3022.BK
		01.3010.CH	01.3011.CH	01.3012.CH	01.3022.CH
	24°	01.3013.WH	01.3014.WH	01.3015.WH	01.3023.WH
		01.3013.BK	01.3014.BK	01.3015.BK	01.3023.BK
		01.3013.CH	01.3014.CH	01.3015.CH	01.3023.CH
	36°	01.3016.WH	01.3017.WH	01.3018.WH	01.3024.WH
		01.3016.BK	01.3017.BK	01.3018.BK	01.3024.BK
		01.3016.CH	01.3017.CH	01.3018.CH	01.3024.CH

Dimming: On/Off, 1-10V, DALI, TRIAC
 UGR: ≤15
 SDCM: ≤3
 Luminous efficacy: 78lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 120mA

