











Tyrone

Fixed trimless Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 120 mm
-  White (WH)
-  Black (BK)



Wattage	Beam Angle	2700K	3000K	4000K	2700~6500K
Max. 15W	15°	10.7013.WH 10.7013.BK	10.7014.WH 10.7014.BK	10.7015.WH 10.7015.BK	10.7029.WH 10.7029.BK
	24°	10.7016.WH 10.7016.BK	10.7017.WH 10.7017.BK	10.7018.WH 10.7018.BK	10.7030.WH 10.7030.BK
	38°	10.7019.WH 10.7019.BK	10.7020.WH 10.7020.BK	10.7021.WH 10.7021.BK	10.7031.WH 10.7031.BK
	50°	10.7022.WH 10.7022.BK	10.7023.WH 10.7023.BK	10.7024.WH 10.7024.BK	10.7032.WH 10.7032.BK

Dimming: On/Off, 1-10V, DALI, TRIAC
 UGR: ≤15
 SDCM: ≤3
 Luminous efficacy: 80lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 350mA

