










# Tyrone

Fixed trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 70 mm
-  White (WH)
-  Black (BK)



Wattage	Beam Angle	2700K	3000K	4000K	2700~6500K
Max. 15W	15°	01.7013.WH	01.7014.WH	01.7015.WH	01.7029.WH
		01.7013.BK	01.7014.BK	01.7015.BK	01.7029.BK
	24°	01.7016.WH	01.7017.WH	01.7018.WH	01.7030.WH
		01.7016.BK	01.7017.BK	01.7018.BK	01.7030.BK
38°	38°	01.7019.WH	01.7020.WH	01.7021.WH	01.7031.WH
		01.7019.BK	01.7020.BK	01.7021.BK	01.7031.BK
50°	50°	01.7022.WH	01.7023.WH	01.7024.WH	01.7032.WH
		01.7022.BK	01.7023.BK	01.7024.BK	01.7032.BK

Dimming: On/Off, 1-10V, DALI, TRIAC  
 UGR: ≤15  
 SDCM: ≤3  
 Luminous efficacy: 80lm/W  
 luminaire Lifetime: 50000h ( L80B50, T a25° C )  
 Material: Aluminium  
 Working Temperature ( °C): -20° C ~ +45° C  
 Transformer availability: LED DC 36V 350mA

