









Tyrone

Fixed trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 70 mm
-  White (WH)
-  Black (BK)



Wattage	Beam Angle	2700K	3000K	4000K	2700~6500K
Max. 10W	15°	01.7001.WH	01.7002.WH	01.7003.WH	01.7025.WH
		01.7001.BK	01.7002.BK	01.7003.BK	01.7025.BK
	24°	01.7004.WH	01.7005.WH	01.7006.WH	01.7026.WH
		01.7004.BK	01.7005.BK	01.7006.BK	01.7026.BK
38°	38°	01.7007.WH	01.7008.WH	01.7009.WH	01.7027.WH
		01.7007.BK	01.7008.BK	01.7009.BK	01.7027.BK
50°	50°	01.7010.WH	01.7011.WH	01.7012.WH	01.7028.WH
		01.7010.BK	01.7011.BK	01.7012.BK	01.7028.BK

Dimming: On/Off, 1-10V, DALI, TRIAC
 UGR: ≤15
 SDCM: ≤3
 Luminous efficacy: 80lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 250mA

