




# Ron

Adjustable trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  L70\*W70 mm
-  0°~15°
-  0°~355°
-  Matte White(MW)
-  Matte Black(MB)
-  Matte Silver(MS)
-  Matte Gold(MG)



Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 10W	15°	02.7517.MW	02.7518.MW	02.7519.MW	02.7520.MW	02.7537.MW
		02.7517.MB	02.7518.MB	02.7519.MB	02.7520.MB	02.7537.MB
		02.7517.MS	02.7518.MS	02.7519.MS	02.7520.MS	02.7537.MS
		02.7517.MG	02.7518.MG	02.7519.MC	02.7520.MG	02.7537.MG
	24°	02.7521.MW	02.7522.MW	02.7523.MW	02.7524.MW	02.7538.MW
		02.7521.MB	02.7522.MB	02.7523.MB	02.7524.MB	02.7538.MB
		02.7521.MS	02.7522.MS	02.7523.MS	02.7524.MS	02.7538.MS
		02.7521.MG	02.7522.MG	02.7523.MG	02.7524.MG	02.7538.MG
	36°	02.7525.MW	02.7526.MW	02.7527.MW	02.7528.MW	02.7539.MW
		02.7525.MB	02.7526.MB	02.7527.MB	02.7528.MB	02.7539.MB
		02.7525.MS	02.7526.MS	02.7527.MS	02.7528.MS	02.7539.MS
		02.7525.MG	02.7526.MG	02.7527.MG	02.7528.MG	02.7539.MG
	50°	02.7529.MW	02.7530.MW	02.7531.MW	02.7532.MW	02.7540.MW
		02.7529.MB	02.7530.MB	02.7531.MB	02.7532.MB	02.7540.MB
		02.7529.MS	02.7530.MS	02.7531.MS	02.7532.MS	02.7540.MS
		02.7529.MG	02.7530.MG	02.7531.MG	02.7532.MG	02.7540.MG

Dimming: On/Off, 1-10V, DALI, TRIAC  
 UGR: ≤15  
 SDCM: ≤3  
 Luminous efficacy: 78lm/W  
 luminaire Lifetime: 50000h ( L80B50, T a25° C )  
 Material: Aluminium  
 Working Temperature ( °C): -20° C ~ +45° C  
 Transformer availability: LED DC 36V 250mA

