


OT

Adjustable trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 45 mm
-  0°~90°
-  0°~355°
-  White (WH)
-  Black (BK)
-  Chrome (CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 8W	15°	03.3501.WH 03.3501.BK 03.3501.CH	03.3502.WH 03.3502.BK 03.3502.CH	03.3503.WH 03.3503.BK 03.3503.CH	03.3504.WH 03.3504.BK 03.3504.CH	03.3513.WH 03.3513.BK 03.3513.CH
	24°	03.3505.WH 03.3505.BK 03.3505.CH	03.3506.WH 03.3506.BK 03.3506.CH	03.3507.WH 03.3507.BK 03.3507.CH	03.3508.WH 03.3508.BK 03.3508.CH	03.3514.WH 03.3514.BK 03.3514.CH
	36°	03.3509.WH 03.3509.BK 03.3509.CH	03.3510.WH 03.3510.BK 03.3510.CH	03.3511.WH 03.3511.BK 03.3511.CH	03.3512.WH 03.3512.BK 03.3512.CH	03.3515.WH 03.3515.BK 03.3515.CH

Dimming: On/Off, 1-10V, DALI, TRIAC
 UGR: ≤13
 SDCM: ≤3
 Luminous efficacy: 80lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 200mA

