


# OT

Adjustable trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Lens
-  Class II
-  Ø 45 mm
-  0°~90°
-  0°~355°
-  White(WH)
-  Black(BK)
-  Chrome(CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K	2700~6500K
Max. 15W	15°	03.4513.WH 03.4513.BK 03.4513.CH	03.4514.WH 03.4514.BK 03.4514.CH	03.4515.WH 03.4515.BK 03.4515.CH	03.4516.WH 03.4516.BK 03.4516.CH	03.4528.WH 03.4528.BK 03.4528.CH
	24°	03.4517.WH 03.4517.BK 03.4517.CH	03.4518.WH 03.4518.BK 03.4518.CH	03.4519.WH 03.4519.BK 03.4519.CH	03.4520.WH 03.4520.BK 03.4520.CH	03.4529.WH 03.4529.BK 03.4529.CH
	36°	03.4521.WH 03.4521.BK 03.4521.CH	03.4522.WH 03.4522.BK 03.4522.CH	03.4523.WH 03.4523.BK 03.4523.CH	03.4524.WH 03.4524.BK 03.4524.CH	03.4530.WH 03.4530.BK 03.4530.CH

Dimming: On/Off, TRIAC, 1-10V, DALI  
 UGR: ≤ 13  
 SDCM: ≤ 3  
 Luminous efficacy: 80lm/W  
 luminaire Lifetime: 50000h ( L80B50, T a25° C )  
 Material: Aluminium  
 Working Temperature ( °C): -20° C ~ +45° C  
 Transformer availability: LED DC 36V 350mA

