


OT

Adjustable trim Downlight

-  Ceiling recessed
-  AC 220V~240V
-  Ra 95
-  Reflector
-  Class II
-  Ø 45 mm
-  0°~90°
-  0°~355°
-  White (WH)
-  Black (BK)
-  Chrome (CH)



| Wattage | Beam Angle | 2700K | 3000K | 3500K | 4000K |
|----------|------------|--|--|--|--|
| Max. 18W | 15° | 03.5501.WH 03.5501.BK 03.5501.CH | 03.5502.WH 03.5502.BK 03.5502.CH | 03.5503.WH 03.5503.BK 03.5503.CH | 03.5504.WH 03.5504.BK 03.5504.CH |
| | 24° | 03.5505.WH 03.5505.BK 03.5505.CH | 03.5506.WH 03.5506.BK 03.5506.CH | 03.5507.WH 03.5507.BK 03.5507.CH | 03.5508.WH 03.5508.BK 03.5508.CH |
| | 36° | 03.5509.WH 03.5509.BK 03.5509.CH | 03.5510.WH 03.5510.BK 03.5510.CH | 03.5511.WH 03.5511.BK 03.5511.CH | 03.5512.WH 03.5512.BK 03.5512.CH |

Dimming: On/Off, TRIAC, 1-10V, DALI
 UGR: ≤13
 SDCM: ≤3
 Luminous efficacy: 80lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: LED DC 36V 450mA

