


OT (1.5 SERIES)

-  Ceiling Track
-  DC 48V
-  Ra 95
-  Reflector
-  Class III
-  0°~90°
-  0°~355°
-  White(WH)
-  Black(BK)
-  Chrome(CH)



Wattage	Beam Angle	2700K	3000K	3500K	4000K
Max. 25W	15°	32.6501.WH 32.6501.BK 32.6501.CH	32.6502.WH 32.6502.BK 32.6502.CH	32.6503.WH 32.6503.BK 32.6503.CH	32.6504.WH 32.6504.BK 32.6504.CH
	24°	32.6505.WH 32.6505.BK 32.6505.CH	32.6506.WH 32.6506.BK 32.6506.CH	32.6507.WH 32.6507.BK 32.6507.CH	32.6508.WH 32.6508.BK 32.6508.CH
	36°	32.6509.WH 32.6509.BK 32.6509.CH	32.6510.WH 32.6510.BK 32.6510.CH	32.6511.WH 32.6511.BK 32.6511.CH	32.6512.WH 32.6512.BK 32.6512.CH

Dimming: On/Off, Knob
 UGR: ≤16
 SDCM: ≤3
 Luminous efficacy: 74lm/W
 luminaire Lifetime: 50000h (L80B50, T a25° C)
 Material: Aluminium
 Working Temperature (°C): -20° C ~ +45° C
 Transformer availability: DC 48V

